ACME Roof Curbs RPS **Technical Product Information** CURB O.D. 19-1/2" x 19-1/2" P.O. NUMBER **STANDARD CONSTRUCTION** CUSTOMER _____ •18 GAUGE GALVANIZED STEEL •1-1/2", 3LB. DENSITY FIBERGLASS INSULATION WOOD NAILER FLUSH UNITIZED CONSTRUCTION PROJECT CONTINUOUS WELDED CORNER SEAMS LOCATION _____ FITS ARCHITECT • PRN 118 • PRN 126 • PRN 135 • PRN 145 • PV 075 • PV 085 • PV 100 • PV 120 • PV 135 19-1/2" x 19-1/2 19-1/2" x 19-1/2" 16-1/2" 19-1/2" x 19-1/2" 16-1/2" х 墳 16-1/2" 16-1/2" Х 16-1/2" х 16-1/2" UNER VALABLE 11" STD. "R" OR AS REQUIRED LINER _____ LINER AVAILABLE st: stb. ar sto THIC RIG 1:" THICK 3LB. RIGID INSULATION 11" THICK 3LB RIGID INSULATION DAMPER OPENING DAMPER OPENING DAMPER OPENING RC-2A RC-3A RC-4A

PROJECT REQUIREMENTS							
QTY.	STYLE	* OVERALL HEIGHT	"R" DIM.	PITCH REQUIREMENTS			
				LONG SIDE	SHORT SIDE	DAMPER OPENING	TAG

ROOF PRODUCTS & SYSTEMS • 484 N. THOMAS DRIVE • BENSENVILLE, IL 60106 • TEL: (630) 595-7320 • FAX: (630) 766-5259