

Metal Construction Roof Curbs

Technical Product Information

RC-7 Style

P.O. NUMBER	STANDARD CONSTRUCTION				
CUSTOMER		•18 GAUGE GALVALUME® STEEL •1-1/2", 3LB. DENSITY FIBERGLASS INSULATION			
		•UNITIZED CONSTRUCTION•BUILT-IN CRICKET•CONTINUOUS WELDED WATERTIGHT SEAMS			
LOCATION					
ARCHITECT		STARTING CAP CELL LOCATION			
	ę	"S" = CAP CELL TO STRADDLE CENTER LINE "C" = CAP CELL CENTERED ON CENTER LINE			
	WELDED	CONDITION 1 SEPARATE CAP CELLS (**= 6")			
3"		CONDITION 2 UNDER/UNDER			
8*		CONDITION 3 OVER/OVER			
+		CONDITION 4 OVER/UNDER			
		O.D			
O.D.	O.D. 3*	LINER (AVAILABLE)			
3***		1 1/2* THICK 3 LB. RIGID INSULATION			
Ī	PLAN VIEW	TYPICAL SECTION			

* NOTE: STANDARD OVERALL HEIGHT 8" UNLESS SPECIFICALLY SHOWN BELOW

PROJECT REQUIREMENTS										
	ACTUAL DIMENSIONS		*	0, 0.		PITCH REQUIREMENTS				
QTY.	O.D.	I.D.	OVERALL HEIGHT	"S"	"C"	LONG SIDE	SHORT SIDE	TAG		

ROOF PRODUCTS & SYSTEMS • 815 KIMBERLY DRIVE • CAROL STREAM, IL 60188 • TEL: (800) 624-8642 • FAX: (866) 466-9335