

Special Application Curbs

Technical Product Information

Special Details for All Curbs

P.O. NUMBER	STANDARD CONSTRUCTION
CUSTOMER	•1-1/2", 3LB. DENSITY FIBERGLASS INSULATION
PROJECT	
LOCATION	"B"STYLEHORIZONTALOVERHANG •UNITIZED CONSTRUCTION •CONTINUOUS WELDED CORNER SEAMS
ARCHITECT	AVAILABLE WITH ANY RPS CURB STYLE
	STD * STD * 8" RC-2A RC-3A
O.D.	STD * STD * 8" VIEW RC-4A RC-5A
*	AS REQUIRED STD *
SIDE SQUARING CORNER GUSSET DETAIL	SECTION A-A SPLICE PLATE DETAIL OVERHANGING WOOD NAILER
NOTE: 14 GAUGE GUSSETS TOP & BOTTOM OF CURB (2PER CORNER) FULLY SEAM WELDED TO SIDE OF CURB SHELL. INSULATION SPLIT FOR GUSSETS 8"LONG GUSSETS SIDE VIEW TOP VIEW	PRE PUNCHED 5/8" DIA. HOLES PRE PUNCHED 5/8" DIA. HOLES B STYLE OPTION FOR FIELD INSTALLED EXTERIOR INSULATION BY OTHERS OTHERS OTHERS OTHERS
	OJECTREQUIREMENTS

	PROJECT REQUIREMENTS											
QTY.	STYLE	ACTUAL DII		*	"B" STYLE NAILER OVERHANG	"R" DIM.	PITCH REQUIREMENTS					
		O.D.	I.D.	OVERALL HEIGHT			LONG SIDE	SHORT SIDE	TAG			

ROOF PRODUCTS & SYSTEMS • 815 KIMBERLY DRIVE • CAROL STREAM, IL 60188 • TEL: (800) 624-8642 • FAX: (866) 466-9335